

STAND-UP OPERATION. STAND-OUT QUALITY.

A NATURAL, INTUITIVE RIDE THE ENTIRE DAY

When mowing, comfort is key. That's why the V-Ride II™ is designed to deliver unrivaled performance and a smooth riding position the entire day! The optimized operator platform with first-class suspension minimizes operator fatigue so the last job of the day feels as smooth as the first.



FEATURES & SPECIFICATIONS

- 1 Strong, reliable Ogura PTO clutch engages and disengages the blades quickly and easily with adjustable air gap for long life. Models with 37 hp or more feature a SoftStart Electric Clutch Controller.
- 2 Powerful and efficient commercial-grade V-Twin engines provide smooth, reliable power. EFI options deliver exceptional fuel efficiency and dependable performance.
- 3 Heavy-duty canister air filter available on select models.
- Heavy-duty steel frame construction ensures a solid foundation for long life.
- Tiger Eye™ Advanced Monitoring System keeps a constant, real-time "eye" on important system functions of the V-Ride II. (Specific functions vary by mower model and engine. Not available on 32" or 36" models.)
- Productive ground speeds help get the job done fast: up to 10.5 mph on most models; up to 8.5 mph on 32" and 36" models.

- Large 8-gallon fuel tank (6.75-gallon fuel tank on the 36" and 5-gallon on the 32" models). All models feature large, angled filler neck and fuel gauge for operator convenience.
- Flat-free (semi-pneumatic) front caster tires eliminate downtime and expense caused by flat tires.



V-RIDE II



Ergonomic operator controls provide incredible ease-of-use along with maximum comfort. Intuitive control design minimizes the learning curve for new operators.



Easily change cutting heights in the field with no tools (1½" to 4½" in ¼" increments). Deck can be lifted from the operating position with the pull of a spring-assisted lever.



Easy-to-reach, full-featured instrument panel features the Tiger Eye Advanced Monitoring System, which keeps a constant, real-time "eye" on important system functions of the V-Ride II. (Specific functions vary by mower model and engine. Not available on 32" or 36" models.)



Spacious operator platform with adjustable suspension delivers a smooth ride and reduces operator fatigue. Extra-large comfort cushion allows for comfortable operation, hour after hour. Adjustable platform suspension further enhances operator comfort.



Comfort cushion and lower panel are removable to allow quick and easy service access to the hydraulic system.



Rugged dual hydraulic drive system delivers dependable power with 12 cc Hydro-Gear® pumps with cooling fans; 10 cc pumps on 32" and 36" V-Ride II.

Actual product may differ from photos.



	V-RIDE XL	V-RIDE II
Total Fuel Capacity	12 gallons	5 gallons (32"), 6.75 gallons (36"), 8 gallons (48", 52" and 61")
Drive Tires	24" x 9.5"-12" (52"), 24" x 12"-12" (61" and 72")	20" x 6.5"-10" (32"), 20" x 8"-10" (36"), 24" x 9.5"-12" (48" and 52"), 24" x 12"-12" (61")
Caster Tires	13" x 6.5"-6"	11" x 4"-5" (32" and 36"), 13" x 5"-6" (48" and 52"), 13" x 6.5"-6" (61")
Drive System Type	Dual Pump and Motor	Dual Pump and Motor
Pumps	Hydro-Gear 16 cc	Hydro-Gear 10 cc (32" and 36"), Hydro-Gear 12 cc (48", 52" and 61")
Motors	Hydro-Gear 18 ci	Parker: 12 ci (32" and 36"), Parker: 14 ci (48", 52" and 61")
Forward Ground Speed	Up to 11.6 mph	8.5 mph (32" and 36"), 10.5 mph (48", 52" and 61")
Reverse Ground Speed	5 mph	5 mph
Parking Brake	Hand lever	Hand lever
Cutting Widths	52", 61" and 72"	32", 36", 48", 52" and 61"
Deck Type	Velocity Plus™ cutter deck	Advantage (32" and 36"), Velocity Plus™ cutter deck (48", 52" and 61")
Cutting Height	2" to 6" in .25" increments	1.5" to 4.5" in .25" increments
Deck Lift	Hand lever	Hand lever
Deck Construction	Tri-plate cutter deck constructed of 3 steel plates totaling nearly 1/2" of steel. Reinforcement plates at cutter deck spindles.	Tri-plate cutter deck constructed of 3 steel plates totaling nearly 1/2" of steel. Reinforcement plates at cutter deck spindles. 32" model features dual-plate.
Deck Spindles	Cast-iron housing with tapered roller bearings	Cast-iron housing with tapered roller bearings
Blade Engagement	Ogura 3.5 (250 ft lb) Adjustable air-gap for extended life.	Ogura GT2.5 (150 ft lb) – (32", 36", 48" and 52") Ogura GT3.5 (250 ft lb) – (61") Adjustable air-gap for extended life.

	MODEL NUMBER	DECK WIDTH	ENGINE	HP*
V-RIDE XL™	SVRXL-52V-38FX-EFI ■	52"	Kawasaki® FX Series EFI – electronic fuel injection	38
	SVRXL-52V-40BV-EFI ■		Vanguard™ BIG BLOCK™ EFI – electronic fuel injection	40
	SVRXL-61V-38CV ■	61"	Kohler® Command PRO®	38
	SVRXL-61V-38FX-EFI ■		Kawasaki® FX Series EFI – electronic fuel injection	38
	SVRXL-61V-40BV-EFI ■		Vanguard™ BIG BLOCK™ EFI – electronic fuel injection	40
	SVRXL-72V-38FX-EFI ■	72"	Kawasaki® FX Series EFI – electronic fuel injection	38
	SVRXL-72V-40BV-EFI ■		Vanguard™ BIG BLOCK™ EFI – electronic fuel injection	40
V-RIDE II™	SVRII-32A-16FX	32"	Kawasaki® FX Series	16
	SVRII-32A-23BV		Vanguard™	23
	SVRII-36A-19FX	36"	Kawasaki® FX Series	19
	SVRII-36A-23BV		Vanguard™	23
	SVRII-48V-22FX	48"	Kawasaki® FX Series	22
	SVRII-48V-23CV		Kohler® Command PRO®	23
	SVRII-48V-25CV-EFI		Kohler® Command PRO® EFI – electronic fuel injection	25
	SVRII-52V-23FX	52"	Kawasaki® FX Series	23
	SVRII-52V-25CV-EFI		Kohler® Command PRO® EFI – electronic fuel injection	25
	SVRII-52V-26FT-EFI		Kawasaki® FT Series EFI – electronic fuel injection	26
	SVRII-52V-37BV-EFI		Vanguard™ BIG BLOCK™ EFI – electronic fuel injection	37
	SVRII-61V-26CV-EFI	61"	Kohler® Command PRO® EFI – electronic fuel injection	26
	SVRII-61V-38CV-EFI		Kohler® Command PRO® EFI – electronic fuel injection	38
	SVRII-61V-38FX-EFI		Kawasaki® FX Series EFI – electronic fuel injection	38.5
	SVRII-61V-40BV-EFI		Vanguard™ BIG BLOCK™ EFI – electronic fuel injection	40

Model lineup is subject to change. Check Scag.com and consult with your local Scag Dealer for current availability.
*Engine power levels as rated by the manufacturer. All models subject to availability.

KEY: ■ BLACKOUT EDITION

LEAVE THE WORRY BEHIND

Since Scag® Power Equipment was established in 1983, we’ve built an industry-wide reputation for producing reliable, heavy-duty commercial equipment. We are proud of the quality of our mowers and their well-earned reputation for durability. The Scag warranty policy shows our commitment to you and to the products we manufacture. See your local Scag dealer for details on the warranty policy or reference the Limited Warranty Statement included in your operator’s manual.

	TURF TIGER II™	CHEETAH II™	TIGER CAT® II	PATRIOT™	FREEDOM Z®	LIBERTY Z	SLS	EVZ	V-RIDE XL	V-RIDE II™	SWZT	SWZ	SW	SFCII-30	SFC-21	TURF STORM™ XL	TURF STORM™	AERSTORM™	WINDSTORM™	EXTREME PRO BLOWER	EXTREME BLOWER	CLASSIC BLOWER	TRUCK LOADERS	JACKAL
1-YEAR COMMERCIAL MACHINE WARRANTY*					•									•	•							•		
2-YEAR COMMERCIAL MACHINE WARRANTY*	•	•	•	•				•	•	•	•	•	•			•	•	•	•	•	•	•	•	•
3-YEAR CUTTER DECK SPINDLE WARRANTY*	•	•	•						•	•		•	•											
3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*							•																	
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*	•	•	•	•	•			•	•	•	•	•	•	•	•									
5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*						•																		
90-DAY WEAR ITEM WARRANTY*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
90-DAY RENTAL USE WARRANTY*	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*																								•
ENGINE WARRANTY	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•



TURF TIGER II, CHEETAH II, TIGER CAT II, V-RIDE II, SWZ & SW WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*
Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

3-YEAR CUTTER DECK SPINDLE WARRANTY*
Velocity Plus™ and Advantage™ cutter decks are equipped with the exclusive Scag heavy-duty, cast-iron cutter blade spindle. We ensure our spindle’s dependability, not only through its top-quality construction, but also through complete coverage of parts and labor for the first and second years, and parts only for the third year. Applies to commercial and non-commercial use.

3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*
Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for three years or 500 hours (whichever comes first) of non-commercial use. This warranty covers manufacturing defects for three years or 500 hours (whichever comes first), including parts and labor (excludes wear items).

PATRIOT & SWZT WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

FREEDOM Z & SFC WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

LIBERTY Z WARRANTY

5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

SLS WARRANTY

3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

* Warranty time periods are from the date of purchase, are only applicable to the original owner and are non-transferable. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner’s manual for more details.
** “Non-Commercial” is defined as single-property usage, where the single property is the residence of the owner of the product. If the product is being used on more than the owner’s single property, it is deemed commercial use and this warranty does not apply. Scag Power Equipment reserves the right to deny and/or void this warranty if evidence clearly points to commercial use.
*** Excludes wear items such as belts, tires, battery. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner’s manual for more details. Depending on model. Manufacturer warranties of 1-year or less are doubled. Manufacturer warranties greater than 1-year and less than 5-years are extended to 5 full years in total.

WARRANTIES

AERSTORM AERATOR, TURF STORM SPREADER-SPRAYERS, TRUCK LOADERS, WINDSTORM, EXTREME PRO BLOWER & EXTREME BLOWER WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*
Frame and structural components including frame, blower housing, oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors (where applicable) are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

CLASSIC BLOWER WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*
2-YEAR NON-COMMERCIAL** MACHINE WARRANTY*

JACKAL WARRANTY

2-YEAR OR 2,000-HOUR COMMERCIAL MACHINE WARRANTY*
1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*

ALL PRODUCTS

90-DAY WEAR ITEM WARRANTY & RENTAL USE*
Wear items, including drive belts, blades, hydraulic hoses, tires and batteries, and rental use are warranted for 90 days.

ENGINE WARRANTY
Engines and engine components are covered by the individual engine manufacturer. See engine owner’s manual for warranty period and details.

SCAG EXTENDED WARRANTY PROGRAM***

Scag's new Extended Warranty Program is better than ever. For only a few dollars per month when financed with this machine, you can protect your investment and enjoy peace-of-mind knowing that your Scag equipment is covered for years to come. Consult with your Scag Dealer for more information.