STAND YOUR GROUND

EASY PICKUP. INCOMPARABLE LONGEVITY.

Scag® Skid-Mount Truck Loaders are known for their reliability as they're built to last for years to come. A steel beveled intake nozzle makes debris pickup easy, and balanced blades reduce vibration and engine stress—increasing uptime and of course, your productivity.

- 1 Heavy-duty, all-steel, welded construction.
- 20"-diameter, welded-steel impeller with %"-thick steel blades.
- 3 Replaceable, ¼" wear liners in blower housing.
- Easy rear access to wear plates and impeller.
- Reliable electric start (battery included).
- Adjustable hose boom and spring-pin transport lock.
- Ambidextrous nozzle handle.
- Comes standard with 4" skid risers; swing-away Hitch-Mount option available (TLS20-18BV).
- Stack Extension accessory offers customization to better fit your personal setup.
- Quick-detach hose for quick and easy transport, storage and cleaning.
- Transport-lock pin secures the intake nozzle to the loader when not in use.
- Optional Light Kit available.

BAA DRIAN



HITCH-MOUNT ACCESSORY







TLS20-18BV shown with swing-away TL Hitch-Mount accessory.

See full specifications on page 85. Actual product may differ from photos.



DEBRIS AND TURF MANAGEMENT EQUIPMENT

TRUCK LOADERS





INDUSTRIAL TOW-BEHIND

TOW-BEHIND

Model	TLB25-35BV	TLB25-37CH	TLB25-49KBD	TL20W-26CH-EFI	TL20W-33BV								
Engine	Briggs & Stratton® Vanguard® BIG BLOCK*, V-Twin, electric start	Kohler® Command PRO®, V-Twin, electric start	Kubota®, 4-cylinder, liquid-cooled, electric start	Kohler® Command PRO® EFI, V-Twin, electric start	Briggs & Stratton® Vanguard® BIG BLOCK*, V-Twin								
HP*	35	37	49	26.5	33								
Fuel Capacity / Tank	8.5 gallon	s / steel tank with built-in f	uel gauge	5.5 gallons / plastic tan	k with built-in fuel gauge								
CFM Output	6,781	6,909	7,318	4,6	580								
Frame Construction	All-steel, welded												
Impeller Construction	6,781 6,909 7,318 4,680 All-steel, welded 4-blade, 1/2"-thick blades, all-steel, welded 4-blade, 3/8"-thick blades, all-steel, welded 525" / 9" 20" / 6.5" Removable back panel for easy impeller & wear plate access 10.5" 7.5" Standard: 1/4" steel, replaceable 84" length, 16"-diameter intake hose; 120" length, 12"-diameter intake hose; 0.00												
Impeller Mounting	Vanguard® BIG BLOCK", V-Twin, electric start PRO®, V-Twin, electric start PRO® EFI, V-Twin, electric start Vanguard® BIG V-Twin, electric start Vanguard® BIG V-Twin, electric start V-Twin start start V-Twin starts in start with built-in fue electric start V-Twin starts in the built-in fue electric start V-Twin starts in the built-in fue electric start V-Twin starts in fue V-Twin starts with built-in fue electric start V-Twin												
Impeller Diameter / Width	Vanguard® BIG BLOCK", V-Twin, electric start PRO®, V-Twin, electric start liquid-cooled, electric start PRO® EFI, V-Twin, electric start Vanguard® BIG V-Twin, electric start 35 37 49 26.5 33 8.5 gallons / steel tank with built-in fuel gauge 5.5 gallons / plastic tank with built-in fuel gauge 4.680 All-steel, welded 4-blade, 1/2"-thick blades, all-steel, welded 4-blade, 3/8"-thick blades, all-steel, welded 4-blade, 3/8"-thick blades, all-steel, welded 4-blade, 3/8"-thick blades, all-steel, welded 25" / 9" 20" / 6.5" Removable back panel for easy impeller & wear plate access 10.5" 7.5" Standard: 1/4" steel, replaceable 84" length, 16"-diameter intake hose; 0.0 dash blue thermoplastic rubber, wire helix with wearstrip 120" length, 12"-diameter intake hose; 0.0 thermoplastic rubber, wire helix with wearstrip Hitch: At least Class III rating Clear thermoplastic, 8" diameter Commercial-grade, all-steel mechani plastic debris cover Yes – optional Roadside Package Yes – optional Roadside Package avaire + 3,500 lb Heavy-duty Dexter Torflex® axle - 3,500 lb Heavy-duty Dexter Torflex® axle - 2,00												
Blower Housing Construction	Removable back panel for easy impeller & wear plate access												
Blower Housing Width		10.5"	7.5"										
Blower Housing Wear Plates	Standard: 1/4" steel, replaceable												
Hose													
Unit Mounting	Н	itch: At least 10,000 lb ratii	Hitch: At least Class III rating										
Discharge Tube	Clear thermoplastic, 8" diameter												
Throttle Control	Comme	ercial-grade, all-steel mech	anicals										
Highway Ready**	Yes	– standard Roadside Pack	age	Yes – optional Roadside Package available									
Axle	Heavy-o	duty Dexter Torflex® axle -	3,500 lb	Heavy-duty Dexter Torflex® axle - 2,000 lb									
Tires		205 / 75	el wheels										
Trailer Width	Yes – standard Roadside Package Heavy-duty Dexter Torflex® axle - 2,0 205 / 75 R15 highway tires with steel wheels												
Height		11	0"										
Weight	1,70	0 lb	2,300 lb	990 lb 1,060 lb									
Warranty	2-Ye	ear Commercial; 90-Day Re	ntal										

^{*}Engine power levels as rated by the manufacturer. All models subject to availability.







INDUSTRIAL SKID-MOUNT

SKID-MOUNT

			ואסטויו שואנ							
Model	TLS20W-29BV	TLS20W-33BV	TLS20-18BV							
Engine	Briggs & Stratton® Vanguard® BI	G BLOCK™, V-Twin, electric start	Briggs & Stratton® Vanguard®, V-Twin, electric start							
HP*	29	33	18							
Fuel Capacity / Tank	5.5 gallons / plastic tanl	k with built-in fuel gauge	1.75 gallons / engine-mounted metal tank							
CFM Output	4,6	80	3,075							
Frame Construction	All-steel, welded									
Impeller Construction	4-blade, 3/8"-thick blades, all-steel, welded									
Impeller Mounting	Tapered locking hub									
Impeller Diameter / Width	20" /	6.5"	20" / 5.25"							
Blower Housing Construction	Removable back panel for easy impeller and wear plate access									
Blower Housing Width	7.	5"	6"							
Blower Housing Wear Plates	Standard: 1/4" steel, replaceable									
Hose	120" length, 12"-diameter quick-detach intake hose; 0.045 black									
Unit Mounting		4" steel s	kid risers							
Discharge Tube	Clear thermoplastic, 8" diameter Clear thermoplastic, 7" diameter									
Throttle Control	Commercial-grade, all-steel mechanicals, plastic debris cover									
Height	75" (without skid mount attached) 74.25" (without skid or hitch mount attach									
Weight	675 lb 437 lb									
Warranty	2-Year Commercial; 90-Day Rental									

^{*}Engine power levels as rated by the manufacturer. All models subject to availability.



^{**} Reference your local regulations to ensure compliance.

COMMITTED TO OUALITY

LEAVE THE WORRY BEHIND

Since Scag® Power Equipment was established in 1983, we've built an industry-wide reputation for producing reliable, heavy-duty commercial equipment. We are proud of the quality of our mowers and their well-earned reputation for durability. The Scag warranty policy shows our commitment to you and to the products we manufacture. See your local Scag dealer for details on the warranty policy or reference the Limited Warranty Statement included in your operator's manual.

	TURF TIGER II"	CHEETAH II"	TIGER CAT" II	PATRIOT"	FREEDOM Z"	LIBERTY" Z	575	EVZ	V-RIDE XL	V-RIDE II"	SWZT	ZMS	SW	SFCII-30	SFC-21	TURF STORM" XL	TURF STORM"	AERSTORM"	WINDSTORM®	EXTREME PRO BLOWER	EXTREME BLOWER	CLASSIC BLOWER	TRUCK LOADERS	JACKAL
1-year Commercial Machine Warranty*					•									•	•							•	più L	
2-YEAR Commercial Machine Warranty*				•				•	•		•											•	•	•
3-YEAR CUTTER DECK SPINDLE WARRANTY*		•							•	•		•	•											
3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*							•																	
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*	•	•	•	•	•		-	•	•	•	•		•	•	•									
5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*																								
90-DAY WEAR ITEM WARRANTY*		•	•	•	•	•	•	•	•	•	•	./		•	•	•	•	.			•/	•		•
90-DAY RENTAL USE WARRANTY*	•			•	•			•	•	•	•	•	•	•	•	•			•			•	•	•
1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*																								•
ENGINE WARRANTY		•	•	•	•	•	•		•		•	•	•		•	•	•	•			•	•	•	•



WARRANTIES

TURF TIGER II, CHEETAH II, TIGER CAT II, V-RIDE II, SWZ & SW WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*

Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

3-YEAR CUTTER DECK SPINDLE WARRANTY*

Velocity Plus™ and Advantage™ cutter decks are equipped with the exclusive Scag heavy-duty, cast-iron cutter blade spindle. We ensure our spindle's dependability, not only through its top-quality construction, but also through complete coverage of parts and labor for the first and second years, and parts only for the third year. Applies to commercial and non-commercial use.

3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*
Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for three years or 500 hours (whichever comes first) of non-commercial use. This warranty covers manufacturing defects for three years or 500 hours (whichever comes first), including parts and labor (excludes wear items).

PATRIOT & SWZT WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

FREEDOM Z & SFC WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

LIBERTY Z WARRANTY

5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

SLS WARRANTY

3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

AERSTORM AERATOR, TURF STORM SPREADER-SPRAYERS, TRUCK LOADERS, WINDSTORM, EXTREME PRO BLOWER & EXTREME BLOWER WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*

Frame and structural components including frame, blower housing, oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors (where applicable) are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

CLASSIC BLOWER WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*
2-YEAR NON-COMMERCIAL** MACHINE WARRANTY*

JACKAL WARRANTY

2-YEAR OR 2,000-HOUR COMMERCIAL MACHINE WARRANTY*
1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*

ALL PRODUCTS

90-DAY WEAR ITEM WARRANTY & RENTAL USE*
Wear items, including drive belts, blades, hydraulic hoses,
tires and batteries, and rental use are warranted for 90 days.

ENGINE WARRANTY

Engines and engine components are covered by the individual engine manufacturer. See engine owner's manual for warranty period and details.

SCAG EXTENDED WARRANTY PROGRAM***

Scag's new Extended Warranty Program is better than ever. For only a few dollars per month when financed with this machine, you can protect your investment and enjoy peace-of-mind knowing that your Scag equipment is covered for years to come. Consult with your Scag Dealer for more information.

^{*} Warranty time periods are from the date of purchase, are only applicable to the original owner and are non-transferable. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner's manual for more details.

^{** &}quot;Non-Commercial" is defined as single-property usage, where the single property is the residence of the owner of the product. If the product is being used on more than the owner's single property, it is deemed commercial use and this warranty does not apply. Scag Power Equipment reserves the right to deny and/or void this warranty if evidence clearly points to commercial use.

^{***} Excludes wear items such as belts, tires, battery. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner's manual for more details. Depending on model. Manufacturer warranties of 1-year or less are doubled. Manufacturer warranties greater than 1-year and less than 5-years are extended to 5 full years in total.