

SOILS

H24
CABIN
(Hydrostatic)



Tough. Rugged. Value



ALL STANDARD FEATURES



**STANDARD HYDRAULIC
REAR REMOTES**



**STANDARD REAR
SWING DRAWBAR**




**STANDARD
MID PTO**



**STANDARD
SEAT**



**STANDARD
FLOOR MAT**



CRUISE CONTROL



**INTEGRATED LOADER
JOYSTICK**



**STANDARD PROJECTOR
HEADLAMPS**



**100%
METAL HOOD**



**STANDARD
FRONT TOW HOOK**



www.solistractorusa.com

SPECIFICATIONS

| FEATURES | | H24 CABIN |
|---|-------------------------------------|-----------|
| ENGINE | | |
| Engine Model | Mitsubishi S3L2 | |
| HP Category | 24 HP | |
| No. of Cylinder | 3 | |
| Aspiration | Natural | |
| Cubic Capacity (Ci) | 80.42 | |
| Rated RPM | 2500 | |
| Max Torque | 76.3Nm@2000 | |
| TRANSMISSION | | |
| Drive | 4WD | |
| Forward/Reverse Controls | Twin Touch Pedals | |
| Gearbox | HST (2 Range) | |
| Transmission Type | Constant Mesh | |
| Cruise Control | Yes | |
| BRAKES | | |
| Type | Oil Immersed Brakes | |
| Type of Actuation | Mechanical, Foot Operated | |
| Differential Lock | Standard | |
| PTO | | |
| PTO (RPM) | Rear - 540@2451 Mid PTO - 2100@2438 | |
| PTO Clutch | Wet Type | |
| PTO Actuation | Button Operated | |
| Steering | Power Steering | |
| HYDRAULICS | | |
| 3 Point Linkages | CAT1N | |
| 3 Point Lifting Capacity@ball ends (lbs) | 1323 | |
| Aux Hydraulic Circuit | 1DA (Detent with Float) | |
| Total Hydraulic Flow(GPM) | 3.98 | |
| CAPACITY | | |
| Fuel Tank (Gal) | 7 | |
| DIMENSIONS & WEIGHT (AGRI TIRES) | | |
| Weight (Lbs) | 2775.62 | |
| Wheel Base (In) | 61.8 | |
| Total Length with TPL (In) | 113.98 | |
| Total Width (In) | 49 | |
| Height (In) upto ROPS | 84 | |
| Ground Clearance | 9.44 (Front Axle) | |



| FEATURES | | H24 CABIN |
|--------------|--------------------------------|-----------|
| TIRES | | |
| Industrial | 23x8.50-12 & 33x15.5-16.5 | |
| Turf | 23x8.50-12 & 33x15.5-16.5 | |
| Turf | 25x8.50-14 & 13.6x16 | |
| Agri | 6x12 & 8.3x20 | |
| Agri | 7x14 & 8.3x24 | |
| Radial | 6.5/80-12 & 280/70R18 | |
| Galaxy Pro | 220/55 R12 & 280/70 R16 | |
| R14 | 23x8.50-12 R14T & 12-16.5 R14T | |

| LOADER TECHNICAL SPECIFICATION | | | |
|--|--------|--------|---------|
| Loader Model | HL24-N | HL24-M | 3200 |
| NSL/MSL | NSL | MSL | NSL/MSL |
| Max Lifting height at Pivot Point (in) | 82 | 82 | 85 |
| Clearance with Attachment Dump (in) | 61 | 61 | 61 |
| Reach at Maximum Height (in) | 33 | 34 | 17 |
| Reach at Bucket on Ground (in) | 63 | 63 | 56 |
| Max. Dump Angle (Deg.) | 44 | 42 | 45 |
| Attachment Rollback Angle (Deg) | 31 | 41 | 43 |
| Digging depth below grade (in) | 2.5 | 2.5 | 5.9 |
| Breakout Force at Pivot Point (dig Position) (lbs) | 1565 | 1477 | 1058 |
| Bucket width (in) | 48 | 48 | 52 |
| Lifting capacity to full height at Pivot point (Lbs) | 1500 | 1102 | 926 |

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.

