

EXPAND YOUR CIRCULATION

BREATHE NEW CAPABILITIES INTO YOUR BUSINESS

Extend your services into the spring and fall with the Scag® AerStorm™. It makes aeration simple, easy and fast so you can take on as many jobs as you want. A 30" inch aerating width, easy depth adjustment and a safety feature that lets you raise and lower tines without removing your hands from the steering controls streamline the workflow. The AerStorm also features the Tiger Eye™ Advanced Monitoring System to keep a constant, real-time "eye" on important system functions.



SCAG
POWER EQUIPMENT

FEATURES & SPECIFICATIONS

- 1 Heavy-duty construction ensures years of dependable service and worry-free productivity.
 - 2 Rugged, dual hydraulic drive system delivers dependable power with 10 cc Hydro-Gear® pumps and 14.5 ci Parker wheel motors.
 - 3 Productive ground speeds help get the job done fast: up to 7 mph. Cover up to 2 acres per hour.
- Large 5.5-gallon fuel tank features large filler neck and fuel gauge for operator convenience.
 - Powerful and efficient 23 hp Kohler® Command Pro® engine delivers huge power, along with exceptional efficiency and dependable performance.
 - 30" aerating width allows you to cover more ground in less time, while allowing you to fit through gates.
 - 48 strong, self-cleaning coring tines deliver reliable and continual turf plug extraction.
 - Adjustable hydraulic down-pressure helps to penetrate even the hardest and driest soils to ensure effective aeration performance in all conditions.
 - Center tines are free-rolling to allow for maneuvering around many trees and obstacles while engaged.
 - Large 18" drive tires provide surefooted traction. Flat-free (semi-pneumatic) front caster tires eliminate downtime and expense caused by flat tires.
 - Front and rear tie-down points for easy trailering.
 - Strong warranty: 2-year commercial/90-day rental limited warranty coverage against manufacturing defects.



AERSTORM



AerStorm Drop Seeder attachment allows you to aerate and overseed in a single pass for maximum productivity and profitability. Attachment is preinstalled on DS model, or can be added as an accessory to the base model.



Spacious operator platform with suspension and padded, bolstered cushion for a smooth, comfortable ride. Removable cushion and lower panel allow quick and easy service access to hydro tank and tines.



Ergonomic drive control lever design provides incredible ease-of-use. Easy to reach, full-featured instrument panel for easy viewing and operation.

EASY TINE ADJUSTMENT AND ENGAGEMENT

The Scag AerStorm's approach to tine depth adjustment is simple, quick and easy.

- Simple and intuitive depth selection pin with easy-grip rubber knob.
- Select aerating depths of 1" to 4" in 1/2" increments to meet the needs of each specific property.
- Hydraulic tine engagement (raise and lower) via a convenient foot-activated switch, allowing you to keep your hands on the steering controls for maximum productivity and safety. Tine activation switch on the instrument panel prevents accidental engagement/disengagement while working or transporting.



Actual product may differ from photos.

SPREADER/SPRAYER & AERATOR



	TURF STORM™ XL	TURF STORM™
Model	STS60XL-23BV	STS30-23BV
Total Fuel Capacity	5 gallons; features large filler neck, fuel gauge	4.5 gallons; features large filler neck, fuel gauge
Engine	Briggs & Stratton® Vanguard®	Briggs & Stratton® Vanguard®
HP*	23	23
Drive System Type	Dual hydraulic	Dual hydraulic
Frame Construction	Stainless steel	Stainless steel
Front Wheels	16" caster tires	16" caster tires
Rear Wheels	20" drive tires	20" drive tires
Liquid Capacity	60 gallons (30 each tank)	30 gallons (15 each tank)
Dry/Granular Capacity	220 lb	120 lb
Pumps	Hydro-Gear®: 10 cc	Hydro-Gear®: 10 cc
Motors	Parker 14.5 ci	Parker 14.5 ci
Forward Ground Speed	Up to 8.5 mph	Up to 8.5 mph
Charging System	50 amp	50 amp
Length	67"	65"
Width (spray booms in)	54"	35.5"
Max Width (spray booms out)	82"	65"
Height	50"	50"
Weight (dry weight / tanks & hopper empty)	965 lb	859 lb
Warranty	2-Year Commercial; 2-Year Non-Commercial; 90-Day Rental; limited warranty coverage against manufacturing defects	



	AERSTORM™
Model	AS30-23CV AS30-23CV-DS†
Engine	Kohler® Command Pro
HP*	23.5 HP @ 3600 rpm
Fuel Tank	5.5 gallon (20.8 liters) tank with molded-in cup holder
Drive Wheels/Tires	18 x 6.5 - 8 four-ply pneumatic tubeless, radius edge
Caster Wheels	13 x 6.5 - 6 Flat-Free (semi-pneumatic)
Drive System	Dual hydraulic
Hydro Pumps	Hydro-Gear PG Series, 10 cc
Drive Wheel Motors	Parker 14.5 ci
Forward Speed Range	0 up to 7.0 mph
Reverse Speed Range	0 up to 3.0 mph

WHEELED BLOWERS

SPECIFICATIONS



	WINDSTORM®	EXTREME PRO™	EXTREME™	CLASSIC™
Model	WS23-37BV-EFI	LBXP17-GX390	LBX15-GX270	LBX15-BV10
Engine	Briggs & Stratton® Vanguard® EFI	Honda® GX390	Honda® GX270	Briggs Vanguard™
HP*	37	11.7	8.5	10
CFM Output	Effective CFM: 6,000** Theoretical Peak CFM: 7,500***	2,824	2,293	1,392
Electric Clutch	Ogura GT3.5 (250 ft lb) with SoftStart Electric Clutch Controller	n/a		
Frame Construction	All-steel, welded 10-gauge			
Impeller Construction	All-steel, welded, 8-blade, dynamically balanced	All-steel, welded, 6-blade, dynamically balanced		All-steel, welded, 4-blade, dynamically balanced
Impeller Mounting	Tapered locking hub			Keyed crankshaft, bolt with thread-lock
Impeller Diameter / Width	23" / 8.5"	17" / 4.25"	15" / 4.25"	15" / 3.5"
Housing Construction	All-steel, welded, 12-gauge front and side housing plate and 10-gauge back housing plate	All-steel, welded, 10-gauge front and back housing plates; 12-gauge skirt		
Housing Width	10"	6.0"		4.5"
Blower Tilt Angle	16 degrees of total vertical tilt; 180 degrees of left/right horizontal rotation	2-degree tilt at discharge; allows blower to more effectively get under wet, heavy debris		
Handlebar	n/a	Tubular steel with thick, comfortable foam grip; 3-position, adjustable height		4-point iso-mount handlebar
Vibration Control	n/a	8-point iso-mount handlebar		4-point iso-mount handlebar
Discharge Opening	69 square inches	25.25 square inches		16 square inches
Discharge Control, Front/Side	Nozzle Direction System features a separate auto left/right switch and fine-tune switch for up to 180 degrees of rotation	Quick-lever located near discharge		
Discharge Control, Angle	Located for easy reach from operator's position; up to 16 degrees of vertical tilt adjustment	Discharge angle control via remote lever on handlebar		n/a
Axle	n/a	3/4"-diameter steel		
Front Wheel(s)	13" x 5"-6", flat-free	4.10" x 3.5" pneumatic tire	9" x 3.5" pneumatic tire	1.5" x 6" flat-free tire
Rear Wheels	24" x 9.5"-12", 4-ply	13" x 5"-6" pneumatic Turf Safe tires	4.10" x 3.5" pneumatic Turf Safe tires	
Length	71.50"	52"	56"	43"
Width	51"	30.25"	28"	27"
Weight	943 lb	190 lb	160 lb	105 lb
Warranty	2-Year Commercial; 90-Day Rental	2-Year Commercial; 90-Day Rental		1-Year Commercial; 2-Year Non-Commercial; 90-Day Rental

* Engine power levels as rated by the manufacturer. All models subject to availability.

** Effective CFM: Calculation obtained by applying accepted engineering methods of measuring overall average airflow volume. This is the default figure published by Scag® for all of its blowers and truck loaders. Learn more at [Scag.com/pro-tip/cfm-definition](https://scag.com/pro-tip/cfm-definition).

*** Theoretical Peak CFM: Figure derived by assuming the highest single-point measurement obtained during testing would apply to the overall airflow volume calculation. This figure is published by some other brands of blowers as their default "CFM" measurement.



*Engine power levels as rated by the manufacturer. All models subject to availability.

† Includes Drop Seeder Kit attachment.

LEAVE THE WORRY BEHIND

Since Scag® Power Equipment was established in 1983, we've built an industry-wide reputation for producing reliable, heavy-duty commercial equipment. We are proud of the quality of our mowers and their well-earned reputation for durability. The Scag warranty policy shows our commitment to you and to the products we manufacture. See your local Scag dealer for details on the warranty policy or reference the Limited Warranty Statement included in your operator's manual.

	TURF TIGER II™	CHEETAH II™	TIGER CAT™ II	PATRIOT™	FREEDOM Z™	LIBERTY Z™	SLS	EYZ	V-RIDE XL	V-RIDE II™	SWZT	SWZ	SW	SFCII-30	SFC-21	TURF STORM™ XL	TURF STORM™	AERSTORM™	WINDSTORM™	EXTREME PRO BLOWER	EXTREME BLOWER	CLASSIC BLOWER	TRUCK LOADERS	JACKAL
1-YEAR COMMERCIAL MACHINE WARRANTY*					•									•	•								•	
2-YEAR COMMERCIAL MACHINE WARRANTY*	•	•	•	•				•	•	•	•	•	•			•	•	•	•	•	•	•	•	•
3-YEAR CUTTER DECK SPINDLE WARRANTY*	•	•	•						•	•		•	•											
3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*							•																	
3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*	•	•	•	•	•			•	•	•	•	•	•	•	•									
5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*						•																		
90-DAY WEAR ITEM WARRANTY*	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
90-DAY RENTAL USE WARRANTY*	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*																								•
ENGINE WARRANTY	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•



WARRANTIES

TURF TIGER II, CHEETAH II, TIGER CAT II, V-RIDE II, SWZ & SW WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*

Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

3-YEAR CUTTER DECK SPINDLE WARRANTY*

Velocity Plus™ and Advantage™ cutter decks are equipped with the exclusive Scag heavy-duty, cast-iron cutter blade spindle. We ensure our spindle's dependability, not only through its top-quality construction, but also through complete coverage of parts and labor for the first and second years, and parts only for the third year. Applies to commercial and non-commercial use.

3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

Frame and structural components including oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors are covered for three years or 500 hours (whichever comes first) of non-commercial use. This warranty covers manufacturing defects for three years or 500 hours (whichever comes first), including parts and labor (excludes wear items).

PATRIOT & SWZT WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*

3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

FREEDOM Z & SFC WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*

3-YEAR OR 500-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

LIBERTY Z WARRANTY

5-YEAR OR 750-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

SLS WARRANTY

3-YEAR OR 300-HOUR NON-COMMERCIAL** MACHINE WARRANTY*

AERSTORM AERATOR, TURF STORM SPREADER-SPRAYERS, TRUCK LOADERS, WINDSTORM, EXTREME PRO BLOWER & EXTREME BLOWER WARRANTY

2-YEAR COMMERCIAL MACHINE WARRANTY*

Frame and structural components including frame, blower housing, oil reservoirs, fittings, oil coolers, electrical switches and clutches, pulleys, hydraulic pumps and wheel motors (where applicable) are covered for two years of commercial use. This warranty covers manufacturing defects for two years, including parts and labor (excludes wear items).

CLASSIC BLOWER WARRANTY

1-YEAR COMMERCIAL MACHINE WARRANTY*

2-YEAR NON-COMMERCIAL** MACHINE WARRANTY*

JACKAL WARRANTY

2-YEAR OR 2,000-HOUR COMMERCIAL MACHINE WARRANTY*

1-YEAR OR 1,000-HOUR RENTAL USE WARRANTY*

ALL PRODUCTS

90-DAY WEAR ITEM WARRANTY & RENTAL USE*

Wear items, including drive belts, blades, hydraulic hoses, tires and batteries, and rental use are warranted for 90 days.

ENGINE WARRANTY

Engines and engine components are covered by the individual engine manufacturer. See engine owner's manual for warranty period and details.

SCAG EXTENDED WARRANTY PROGRAM***

Scag's new Extended Warranty Program is better than ever. For only a few dollars per month when financed with this machine, you can protect your investment and enjoy peace-of-mind knowing that your Scag equipment is covered for years to come. Consult with your Scag Dealer for more information.

* Warranty time periods are from the date of purchase, are only applicable to the original owner and are non-transferable. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner's manual for more details.

** "Non-Commercial" is defined as single-property usage, where the single property is the residence of the owner of the product. If the product is being used on more than the owner's single property, it is deemed commercial use and this warranty does not apply. Scag Power Equipment reserves the right to deny and/or void this warranty if evidence clearly points to commercial use.

*** Excludes wear items such as belts, tires, battery. Warranty does not cover wear items, misuse, abuse, lack of maintenance, etc. See the Limited Warranty Statement in your owner's manual for more details. Depending on model. Manufacturer warranties of 1-year or less are doubled. Manufacturer warranties greater than 1-year and less than 5-years are extended to 5 full years in total.