

SCAG
POWER EQUIPMENT

TIGER CAT II



#ScagNation Profile



MIKE R.
Amherst, NY

**SCAG OWNER FOR 10 YEARS
COMMERCIAL OPERATOR**

WHY DID YOU CHOOSE SCAG?

"Scag construction is superior to other brands, and they design mowers to be serviceable and to last a very long time. I would never own anything else."



Actual product may differ from photos.

FEATURES & SPECIFICATIONS

- Heavy-duty, tubular-steel frame provides a solid foundation for years of reliable service; replaceable front caster wheel weldment.
- Fabricated, welded and reinforced Velocity Plus™ Cutter Deck is ultrastrong and truly commercial-grade. Tri-Plate deck is nearly ½" thick.
- Powerful drive system features dependable design, while dual 12 cc pumps and high-torque, cast-iron wheel motors ensure reliable power.
- Up to 12 mph forward and 5 mph reverse ground speeds make quick work of tough jobs.
- Low center of gravity delivers sure footing on a variety of terrain.
- Torsion-spring suspension seat adjusts to operator's weight to provide superior comfort. Seat features full padding, forward/rearward adjustment, high back, adjustable armrests and adjustable back angle.
- 4-point, rubber iso-mounting provides additional comfort to the seat.
- Large 24" drive tires ensure solid traction and curb-climbing ability.
- 9.5-gallon approximate fuel capacity for hours of cutting time. Large fuel tank filler neck allows for quick refueling. Fuel tank features a molded-in cup holder for extra convenience.
- Foot-operated parking brake allows the operator to apply the brake without removing hands from the steering controls. Ausco disc brakes for reliable performance.
- Large flat-free caster wheels feature tapered roller bearings for long life. Lip seals keep grease in and dirt out.
- Tough idler pulley system features all-steel pulleys, high-quality bearings and pulley-bearing debris guards for long, reliable service.
- Tiger Eye™ Advanced Monitoring System keeps a constant, real-time "eye" on important system functions of the Tiger Cat® II. (Specific functions vary by mower model and engine.)
- User-friendly design provides simple operation and allows easy access for maintenance.
- Air-filtration systems ensure clean engine air for maximum power and long life; heavy-duty remote canister filter on Kawasaki® FX and Briggs Vanguard® engines.
- All Tiger Cat II models include standard twin-stick steering controls, flat-free front caster tires and foldable Roll-Over Protection System (ROPS).

-
- A variety of accessories are available for the Tiger Cat II, such as:
 - Grass Catchers.
 - Mulching Systems.
 - Trailer Hitch.
 - Tiger Striper Lawn Striping System.
 - Chrome Wheel Covers.
 - LED Light Kit.
 - Operator-Controlled Discharge Chute (OCDC).

See page 53 for additional options.



Operator-friendly instrument panel includes a conveniently located ignition switch, cutter-deck-engagement switch, choke, throttle controls and Tiger Eye Advanced Monitoring System.



High-torque, cast-iron wheel motors ensure dependability. Heavy-duty drive system is designed for reliability.



Heavy-duty Ogura GT3.5 clutch features 250 ft lb of holding strength. Adjustable air gap for long life.



Entire foot plate area lifts to provide complete access to the top of the deck for easy servicing.



Adjustable, 3-position deck-lift foot pedal makes changing the height-of-cut fast and easy. Adjusts from 1" to 5" in ¼" increments.



Rugged 12 cc hydraulic pumps feature pressure-relief valves and top-mounted fans for added reliability and longer life.



TURF TIGER II™

MODEL NUMBER	DECK WIDTH	HP*	ENGINE
STTII-52V-25CH-LP-EFI	52"	25	Kohler® Command PRO® LP – propane-powered, electronic fuel injection
STTII-52V-31BV		31	Briggs Vanguard® BIG BLOCK™
STTII-61V-25CH-LP-EFI	61"	25	Kohler® Command PRO® LP – propane-powered, electronic fuel injection
STTII-61V-25KBD		25	Kubota® – 3-cylinder, diesel-powered
STTII-61V-31BV		31	Briggs Vanguard® BIG BLOCK™
STTII-61V-31DFI		31	Kawasaki® – digital fuel injection, liquid-cooled
STTII-61V-40BV-EFI	72"	40	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection
STTII-72V-25KBD		25	Kubota® – 3-cylinder, diesel-powered
STTII-72V-31DFI		31	Kawasaki® – digital fuel injection, liquid-cooled
STTII-72V-40BV-EFI		40	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection



CHEETAH II™

SCZII-61V-37BV-EFI	61"	37	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection
SCZII-61V-38FX-EFI		38	Kawasaki® FX – electronic fuel injection
SCZII-61RD-38FX-EFI		38	Kawasaki® FX – electronic fuel injection
SCZII-72V-37BV-EFI	72"	37	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection
SCZII-72V-38FX-EFI		38	Kawasaki® FX – electronic fuel injection



TIGER CAT II™

STCII-48V-22FX	48"	22	Kawasaki® FX
STCII-52V-26FT-EFI	52"	26	Kawasaki® FT – electronic fuel injection
STCII-52V-28BV-EFI		28	Briggs Vanguard® BIG BLOCK™
STCII-61V-26FT-EFI	61"	26	Kawasaki® FT – electronic fuel injection
STCII-61V-32BV		32	Briggs Vanguard® BIG BLOCK™



PATRIOT™

SPZ-52H-22FX	52"	22	Kawasaki® FX – V-twin
SPZ-52H-23CV		23	Kohler® Command PRO® – V-twin
SPZ-52H-26BV		26	Briggs Vanguard® – V-twin
SPZ-61H-23FX	61"	23	Kawasaki® FX – V-twin
SPZ-61H-25CV		25	Kohler® Command PRO® – V-twin
SPZ-61H-26BV		26	Briggs Vanguard® – V-twin



FREEDOM Z®

SFZ-48H-24KT	48"	24	Kohler® 7000 Series – V-Twin
SFZ-52H-26KT	52"	26	Kohler® 7000 Series – V-Twin


LIBERTY® Z

MODEL NUMBER	DECK WIDTH	HP*	ENGINE
SZL-36H-18FR	36"	18	Kawasaki® FR – V-twin
SZL-36H-20KT		20	Kohler® 7000 series – V-twin
SZL-42H-22KT	42"	22	Kohler® 7000 series – V-twin
SZL-48H-22KT	48"	22	Kohler® 7000 series – V-twin
SZL-52H-23FR	52"	23	Kawasaki® FR – V-twin
SZL-61H-24FR	61"	26	Kawasaki® FR – V-twin


V-RIDE II™

SVRII-32A-16FX	32"	16	Kawasaki® FX – V-twin
SVRII-36A-19FX	36"	19	Kawasaki® FX – V-twin
SVRII-48V-22FX	48"	22	Kawasaki® FX – V-twin
SVRII-52V-26FT-EFI	52"	26	Kawasaki® FT – electronic fuel injection
SVRII-52V-37BV-EFI		37	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection
SVRII-61V-38FX-EFI	61"	38	Kawasaki® FX – V-twin – electronic fuel injection
SVRII-61V-40BV-EFI		40	Briggs Vanguard® BIG BLOCK™ – electronic fuel injection


SWZ

SWZ-36A-14FS	36"	14	Kawasaki® FS – V-twin
SWZ-48V-15FSE	48"	15	Kawasaki® FS – V-twin, electric-start
SWZ-52V-18FSE	52"	18	Kawasaki® FS – V-twin, electric-start
SWZL-52V-22FSE		22	Kawasaki® FS – V-twin, electric-start
SWZL-61V-22FSE	61"	22	Kawasaki® FS – V-twin, electric-start


SW

SW-32-14FS	32"	14	Kawasaki® FS – V-Twin
SW-36A-14FS	36"	14	Kawasaki® FS – V-Twin
SW-48V-14FS	48"	14	Kawasaki® FS – V-Twin
SW-52V-15FS	52"	15	Kawasaki® FS – V-Twin


SWZT

SWZT-36H-14FS	36"	14	Kawasaki® FS – V-Twin
SWZT-48H-15FSE	48"	15	Kawasaki® FS – V-Twin, electric-start
SWZT-52H-18FSE	52"	18	Kawasaki® FS – V-Twin, electric-start
SWZT-61H-22FSE	61"	22	Kawasaki® FS – V-Twin, electric-start


SFC

SFC-30-7CV	30"	7	Kohler® Command PRO® CV224
SFC-30-7CV-CA		7	Kohler® Command PRO® CV224 (California)
SFC-30-7CV-S (front swivel wheels)		7	Kohler® Command PRO® CV224
SFC-30-7CV-S-CA (front swivel wheels)		7	Kohler® Command PRO® CV224 (California)

Model lineup is subject to change. Check Scag.com and consult with your local Scag Dealer for current availability.

*Engine power levels as rated by the manufacturer. All models subject to availability.