# **HEDGE TRIMMERS**





RedMax offers an extensive line of durable, versatile and easy-to-use hedge trimmers. Case-hardened steel blades reduce the need for sharpening. Double reciprocating blades deliver fast, clean, precise, manicured cuts. And powerful, fuel efficient engines deliver all the performance you need.



High performance and efficient Strato-Charged® engines



Durable, long, ergonomic throttle trigger



Ergonomic vibration dampening handles reduces fatigue



NEW Fully articulating cutting head with 10 fixed positions



Fold to 0-degrees for quick, safe transport



#### CHTZ60

Designed for rugged use by part-time professionals. Multi-position handle and low overall weight allow for easy maneuvering. Durable gearbox and commercial-grade blades are built for high-capacity cutting.



## CHTZ600 (CHTZ600R)

Durable gears and hardened steel blades are built for rugged commercial use. Two-stage air filter reduces maintenance and wear on the engine, ensuring reliable performance. The CHTZ600R is a coarse cutting version of the CHTZ600.



## CHTZ750R

High-torque gears and coarse-cut steel blades are built for demanding, commercial jobs. Two-stage air filter reduces maintenance and wear on the engine, ensuring reliable performance.



### **HTZ750**

Single-sided design allows for more precise trimming, with a debris catcher for quick clean-up. Designed for commercial use, it's fitted with durable gears and hardened steel blades.



# LRTZ235

This articulating hedge trimmer has a 24" blade and 10 locking positions to make it easy to trim professional looking hedges. Fold it to 0-degrees for safer transport to the next jobsite.



## SRTZ235

With its ergonomic, light-weight design and higher fuel capacity, comfortably work all day with fewer trips to the trailer for refueling.



#### STRZ260F

Powerful fixed pole trimmer with double sided cutting. Commercial-grade gearbox is built to withstand the toughest conditions. Patented engine design delivers more power and less fuel consumption compared to conventional engines.

Specifications	CHTZ60	CHTZ600	CHTZ600R	CHTZ750R	HTZ750	SRTZ260F	LRTZ235	SRTZ235
Displacement (cc)	21.7	21.7	21.7	21.7	21.7	25.4	22.5	22.5
Power Output (hp)	0.8	0.8	0.8	0.8	0.8	1.3	1.0	1.0
Blade Length (in.)	24	24	24	30	30	26	24	24
Overall Length (in.)	44	44	44	50	50	76	99.2	73.6
Teeth Opening (in.)	1.1	1.1	1.2	1.2	1.1	1.2	1.0	1.0
Cutting Speed (cuts/min)	4,400	4,400	3,200	3,200	4,400	4,340	4,400	4,400
Dry Weight (lbs)	11.5	10.8	11	11.5	11.2	13.2	13.5	12.5
Warranty	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years	2 Years

